

IP NETWORK CAMERA

Model # - IPD4MIR-T28M



Features

- 4 Megapixel HD Video Resolution
- Outdoor Vandal Rated IP67 & IK10
- IR LED's - up to 90ft
- 2.8mm Fixed Lens
- 3D DNR, True WDR, BLC
- H.265/H.265+ Compression
- Smart Event
 - Line Crossing
 - Intrusion Detection
- Built In Weatherproof Microphone
- Micro SD slot, up to 128GB
- ONVIF Compliant
- PoE

Part Number	IPD4MIR-T28M
Resolution	4 Megapixel (2688 x 1520)
Frame Rate	30fps(2688x1520)
Image Sensor	1/3" Progressive Scan CMOS
Lux Rating	0.028 Lux @ F2.0, 0 Lux with IR
Shutter	1/30s ~ 1/100,000s
Lens	2.8mm Fixed Lens IR Cut Filter
Angle Adjustment	Pan: -90°-90°, Tilt: 0° ~ 75°, Rotation: 0° ~ 355°
IR Range	Up to 90ft
DNR	3D DNR
WDR	True Wide Dynamic Range 120dB
Compression	H.264+ / H.264 / MJPEG/H.265/H.265+
H.264 Codec	Main Profile
Bit Rate	32Kbps ~ 16Mbps
Image Settings	Saturation, Brightness, Contrast, Sharpness
BLC	Configurable by Zone
Network Storage	NAS
Impact Protection	IEC60068-275Eh, 50J; EN50102, up to IK10
Alarm Trigger	Motion, Alarm, Network Disconnect, IP Conflict, Storage Exception
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
Interoperability	ONVIF, ISAPI
Security	User Authentication, Reset Button, Flickerless, Dual Stream, Heartbeat, Mirror, Watermark
Communication	1-RJ45 10M / 100M Ethernet Interface
Operating Temp	-30 °C ~ 60 °C (-22 °F ~140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC ± 10% , PoE (802.3af)
Power Consumpt	Max, 6W
Dimensions	4.4" x 3.2"
Weather Rating	IP67 / IK10