

LTIND2812IR-MZ



FEATURES

IVMS HD-TVI 2MP Turbo HD Indoor Motorized Vari-focal Dome Camera

- 1080P Video Output
- HDTVI Technology
- True Day/Night
- 2.8 - 12mm vari-focal lens
- Motorized Vari-Focal Lens
- OSD menu, 3D DNR, Smart IR
- Up to 90ft IR distance
- True WDR

Specifications	
Model Number	LTIND2812IR-MZ
Image Sensor	2MP CMOS Sensor
Video Format	PAL / NTSC
Effective Pixels	1928(H)*1088(V)
Min. Illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter speed	1/25 s to 1/50,000 s
Lens	2.8-12mm @ F1.2 Motorized, Angle of view: 92° - 32°
Day & Night	ICR
Wide dynamic range	120dB True WDR
Synchronization	Internal synchronization
Video Frame Rate	1920*1080@30fps
HD Video Output	1 Analog HD output

Specifications	
CVBS Output	Yes
S / N Ratio	More than 62dB
AGC	Support
D/N Mode	Color/BW/Smart
White Balance	ATW, MWB
BLC	Support
WDR	True WDR 120dB
Working Temperature / Humidity	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC, 24VAC
Power Consumption	12 VDC Max: 7W 24 VAC Max: 9W
Weather Proof Ratings	IP66
IR Range	Up to 90 ft
Communication	Up the coax(need UTC controller) Protocol: Pelco-C(Coaxitron)
Dimensions	□5.29" x 4.88" x 4.39"
Weight	1.57 lbs
Recess Mount	FLSHMT1
Wall Mount	MTW3
Pole,Corner	P:IPPOLEMT,C:CRNMT