

IP MINI SPEED DOME

IPPTZMINI25X-FL



Features

- Mini Flush Mount Speed Dome
- 2 Megapixel (1920 x 1080)
- 25x Optical Zoom
- 16x Digital Zoom
- Pan Tilt Zoom Control from Recorder/Keyboard
- Wide Dynamic Range
- 360° Endless Pan
- Set Presets, Patrols or Patterns
- 12VAC Power Supply and POE

Model Number	IPPTZMINI25X-FL
Resolution	2 Megapixel (1920 x 1080)
Image Sensor	1/2.8" Progressive Scan CMOS
Effective Pixels	1920(H)x1080(V)
Signal System	PAL/NTSC
Minimum Illumination	Color: 0.05Lux @(F1.6, AGC On), B/W: 0.01Lux @(F1.6, AGC On)
White Balance	Auto/Manual/ATW/Indoor/Outdoor/Daylight lamp/Sodium lamp
AGC	Auto/Manual
S/N Ratio	52dB
Backlight Compensation	HLC/BLC
WDR	Digital WDR
Shutter Time	1/1 ~ 1/10,000s
Day & Night	ICR
Focal Length	4.8 ~ 120mm, 25X
Angle of View	57.6~2.5 degree (Wide-Tele)
Min.Working Distance	10-1500mm(Wide-Tele)
Aperture Range	F1.6-F3.5
Pan & Tilt Pan Range	Pan: 360° endless; Tilt: -10° ~ 90°(Auto Flip)
Pan / Tilt Speed	Pan manual speed: 0.1° ~ 160°/s, Pan preset speed: 160°/s Tilt manual speed: 0.1° ~ 120°/s, Tilt preset speed: 120°/s
Proportional Zoom	Rotation speed automatically adjusted
Number of Preset	256
Patrol	8 patrols, up to 32 presets per patrol
Park Actions	Pattern/Pan scan/Tilt scan/Frame scan/Panorama scan/Random scan
Scheduled Task	Preset / Patrol / Pattern / Pan scan
Video Output	1.0V[p-p] / 75Ω, PAL or NTSC composite, BNC
Audio Input	1 Mic in/Line in, Line input: 2 ~ 2.4V[p-p]; output impedance
Audio Output	1 Audio output interface, Line level, impedance: 600Ω
Ethernet	10Base-T / 100Base-TX, RJ45 connector
Frame Rate	60Hz: 30 fps (1920×1080), 30 fps (1280×720)
Image Compression	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Audio Compression	G.711u /G.711a /G.726 /MP2L2
Protocols	IPv4/IPv6 + 20 more
Simultaneous Live Views	Up to 6
Streams	Dual streams
SD Card	Built-in micro SD card slot, up to 128GB
User/Host Level	Up to 32 users, 3 Levels: Administrator, Operator, User
Security	User authentication, Host authentication, IP address filtering
Compatibility	Open-ended API, support Onvif, PSIA and CGI
Web Browser	IE 7+, Chrome 18+, Firefox 5.0+, Safari 5.02+
Power	12 VDC / POE, Max 20W
Working Temperature	-30°C ~ 65°C (-22°F ~ 149°F)
Humidity	95% or less
Protection Level	IP66, TVS 4,000V lightning protection, surge protection
Dimensions	(6.10"×9.25")
Weight	(4.41 Lbs)

**Specifications and improvements subject to change without notice