

COVERT IP CAMERA

IPBRD1M



Features

- 1 Megapixel Image
- 1280 x 720
- Pinhole 3.2mm Lens
- True Wide Dynamic Range
- True Day & Night
- H.264
- ONVIF Compliant

Part Number	IPBRD1M
Megapixel	1 Megapixel
Resolution	1280 x 720
Frame Rate	30fps(1280 x 720) ~ 30fps(640 x 480)
Image Sensor	1/4" Progressive Scan CMOS
Lux Rating	0.01 Lux @ F1.2 w/AGC On, 0.028 Lux @ F2.0 w/AGC On
Shutter	1/3s ~ 1/100,000s
Lens	3.2mm @ F2.5, 65° Angle of View
DNR	3D DNR
WDR	True Wide Dynamic Range
dB Range	100 dB
Compression	H.264 / MJPEG
H.264	Main Profile
Video Bit Rate	32Kbps ~ 8 Mbps
BLC	Zone Control / Optional
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
Interoperability	ONVIF, PSIA, CGI, ISAPI
Security	User Authentication, Reset Button, Flickerless, Dual Stream, Heartbeat, Mirror, Watermark
Communication	1-RJ45 10M / 100M Ethernet Interface
Dimensions	2.18" x 1.63" x 1.06"
Weight	0.12 lbs
Operating Temp	-22 °F - 140 °F Humidity 95%
Power Supply	12 VDC ± 10%
Power Consumpt	2.3 W
Weather Rating	Indoor