



# IPBT6MIR-MZ



## FEATURES

6MP Motorized Vari-focal EXIR Turret, Exterior

- 6 Megapixel (3072 × 2048) Resolution
- Full HD 1080p real-time video
- True WDR & 3D DNR & BLC
- EXIR illuminator up to 100ft.
- IP67
- PoE

Specifications	
Model Number	IPBT6MIR-MZ
Image Sensor	1/2.9" progressive scan CMOS
Min. illumination	0.018 lux @ F1.6, AGC ON, 0 lux with IR
Shutter time	1/3s ~ 1/100,000s
Lens	2.8mm - 12mm @ F1.6, angle of view: 97° to 33°
Angle adjustment	Pan: 0° ~ 355°, tilt 0° ~ 75°
Digital noise reduction	3D DNR
Wide Dynamic Range	True WDR, 120db
Backlight compensation	Yes, zone configurable
Video compression	H.264 / MJPEG / H.264+ / H.265 / H.265+
Audio input output	Yes
H.264 codec profile	Main profile
Bit rate	32 Kbps ~ 16 Mbps

Specifications	
Dual stream	Yes
Max. image resolution	3072 × 2048
Frame rate	20fps (3072 × 2048), 30fps (2560 x 1440)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
Network storage	NAS
Alarm trigger	Motion detection, tampering alarm
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
System compatibility	ONVIF, PSIA, CGI
General functionalities	User authentication, watermark
Communication interface	1 RJ45 10M/ 100 M Ethernet interface
Operating conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F) humidity 95% or less (non-condensing)
Power supply	12 VDC +/- 10%, PoE (802.3af)
Power consumption	Max, 10W (12.5W with ICR on)
Ingress protection	IP67
EXIR range	up to 100ft
Dimensions	Ø5.35"x5.73"
Weight	2.34lbs.
Wall Mount	MTW4
Pendant Mount	MTPD3
Corner	CRNMT
Pole	IPPOLEMT
Inclined Junction Box	JNBX5-S