

IP NETWORK CAMERA

IPBT13MIR & IPBT3MIR

You Talk, We Listen[®]
USA
ONIX



Features

- Megapixel Recording
 - IPBT13MIR** – 1.3 Megapixel
 - IPBT3MIR** – 3 Megapixel
- Outdoor Rated IP66
- IR LED's – 66ft ~ 99ft Range
- New EX-IR Illuminators
- Digital Wide Dynamic Range
- True Day / Night
- ONVIF Compliant

Part Number	IPBT13MIR	IPBT3MIR
Resolution	1280 x 960	2048 x 1536
Frame Rate	30fps(1280x960) 30fps(1280x720)	15fps(2048x1536) 30fps(1920x1080) 30fps(1280x720)
Image Sensor	1/3" Progressive Scan CMOS	
Lux Rating	0.028 Lux @ F2.0, 0 Lux with IR	
Shutter	1/30s ~ 1/100,000s	
Lens	4mm IR Cut Filter	
Angle Adjustment	2 Axis Pan: 0° ~ 355° Tilt: 0° ~ 65°	
IR Range	20-30 Meter (66ft ~ 99ft)	
DNR	3D DNR	
WDR	Digital WDR	
Compression	H.264 / MJPEG	
H.264 Codec	Main Profile	
Bit Rate	32Kbps ~ 16Mbps	
Image Settings	Saturation, Brightness, Contrast, Sharpness	
BLC	Configurable by Zone	
Impact Protection	IEC60068-275Eh, 50J; EN50102, up to IK10	
Alarm Trigger	Motion, Alarm, Network Disconnect, IP Conflict, Storage Exception	
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos	
Interoperability	ONVIF, PSIA, CGI	
Security	User Authentication, Reset Button, Flickerless, Dual Stream, Heartbeat, Mirror, Watermark	
Communication	1-RJ45 10M / 100M Ethernet Interface	
Operating Temp	-30 °C – 60 °C (-22 °F –140 °F) Humidity 95%	
Power Supply	12 VDC ± 10% , PoE (802.3af)	
Power Consumpt	7W with IR	
Dimensions	140 x 92 mm	
Weather Rating	IP66	