

IP NETWORK CAMERA

IPPH13M

You Talk, We Listen[®]
USA
ONIX



Features

- 1.3 Megapixel Recording
- Wide Dynamic Range – 120dB
- Day / Night
- Covert
- Audio/Alarm IO
- SD Recording up to 64GB
- ONVIF Compliant
- PoE

Part Number	IPPH13M
Resolution	1280 x 960
Frame Rate	30fps(1280x960) 30fps(1280x720)
Image Sensor	1/3" Progressive Scan CMOS
Lux Rating	0.01 Lux @ F1.2 AGC On
Shutter	1/3s ~ 1/100,000s
Lens	3.7mm @ F2.3, Angle of View 63°
Lens Mount	M12
DNR	3D DNR
WDR	120dB
Compression	H.264 / MJPEG/ MPEG4
H.264 Codec	Main Profile / Baseline Profile / High Profile
Third Stream	Independent 60Hz: 30fps(1280x960)
Audio	3.5mm Audio In (Mic in/Line in) / Line Out
Audio Compress	G.711/G.726
Audio Bit Rate	64Kbps(G.711) / 16Kbps(G.726)
Bit Rate	32Kbps ~ 16Mbps
Image Settings	Saturation, Brightness, Contrast, Sharpness
BLC	Configurable by Zone
Network Storage	NAS
Alarm Trigger	Motion, Alarm, Network Disconnect, IP Conflict, Storage Exception
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
Interoperability	ONVIF, PSIA, CGI
Security	User Authentication, Reset Button, Flickerless, Dual Stream, Heartbeat, Mirror, Watermark
Communication	1-RJ45 10M / 100M Ethernet Interface
Dimensions	78mm x 105mm x 32mm
Weight	450g
Operating Temp	-30 °C – 60 °C (-22 °F –140 °F) Humidity 95%
Power Supply	12 VDC ± 10% , PoE (802.3af)
Power Consumpt	Max 6.5W