

IP NETWORK CAMERA

IP360IR3M & IP360IR6M



Features

- Megapixel Recording
IP360IR3M – 3 Megapixel
IP360IR6M – 6 Megapixel
- 360° View
- Multiple Viewing Modes
 -Fisheye
 -Panoramic
 -Virtual PTZ
- 30ft IR Range
- IP66 Outdoor Rated
- ONVIF Compliant
- PoE



Part Number	IP360IR3M	IP360IR6M
Resolution	2048 x 1536	3072 x 2048
High Frame Mode	Fisheye 30fps(2048 x 1536) 4 x PTZ 30fps(800 x 600)	Fisheye 30fps(3072 x 2048) 4 x PTZ 30fps(1024 x 768)
Image Sensor	1/1.8" Progressive Scan CMOS	
Lux Rating	0.05 Lux @ F1.2, 0.3 Lux @ F2.8, 0.0 Lux with IR On	
Shutter	1/25s ~ 1/100,000s	
Lens	1.19mm @ F2.8, Angle of View 360°	
Lens Mount	M12	
IR Range	30ft IR Range	
DNR	3D DNR	
WDR	Digital WDR	
Compression	H.264 / MJPEG / MPEG	
H.264 Codec	Main / Baseline / High Profile	
Bit Rate	32Kbps ~ 16Mbps	
Image Settings	Saturation, Brightness, Contrast, Sharpness, Hue, White Balance	
BLC	Yes	
SD Card	Mini SD Card Supported, Up to 64GB	
Audio Compress	G.711/G.726	
Audio Bit Rate	64Kbps(G.711) / 16Kbps(G.726)	
Audio In/Out	3.5mm Input, Mic in Line in / 3.5mm Output	
Impact Protection	IEC60068-275Eh, 50J; EN50102, up to IK10	
Alarm Trigger	Motion, Alarm, Network Disconnect, IP Conflict, Storage Exception	
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos	
Standard	ONVIF, PSIA, CGI	
Security	User Authentication, Reset Button, Flickerless, Dual Stream, Heartbeat, Mirror, Watermark	
Communication	1-RJ45 10M / 100M Ethernet Interface	
Operating Temp	-30 °C – 60 °C (-22 °F –140 °F) Humidity 95%	
Power Supply	12VDC / PoE 12W	
Dimensions	140mm x 114mm	
Weight	3.08 lbs	