



# '4KN8-8POE' Series

# 8 CHANNEL NETWORK VIDEO RECORDER 8 BUILT-IN POE PORTS PLUG-N-PLAY

#### **FEATURES**

- **HIGH DEFINITION** RECORDS UP TO 12 MEGAPIXEL PER CHANNEL
- **NETWORKABLE** VIEW CAMERAS LOCALLY, OVER WI-FI OR OFF-SITE USING A PC OR SMART PHONE
- PTZ CONTROL CONTROL PAN TILT ZOOM AND MOTORIZED LENS FROM NVR, PHONE OR PC
- LICENSE FREE SOFTWARE OUR RECORDER HAS NO PER CHANNEL LICENSE FEE OR FUTURE FEES
- REMOTE BACK-UP SCHEDULE AN AUTOMATIC BACK-UP OR A MANUAL BACK OF CAMERAS
- FREE CLOUD STORE SAVE EVENTS IN THE CLOUD USING DROPBOX, GOOGLE DRIVE OR ONEDRIVE
- CUSTOM RECORD CONFIGURE EACH CHANNELS RESOLUTION, FRAME RATE AND BIT RATE
- AUDIO TWO-WAY AUDIO, UP TO 16 CHANNELS OF AUDIO, CAMERAS WITH MIC OR AUDIO INPUT
- **COMPRESSION** H.265+, H.265, H.264+ TO INCREASE THE NUMBER OF DAYS THE DVR RECORDS
- WATERMARK HIDDEN WATERMARK ON ALL RECORDED VIDEO FOR VIDEO VERIFICATION
- 4K ULTRA HD OUTPUT 4K ULTRA HD HDMI OUTPUT FOR CRYSTAL CLEAR IMAGES
- SPOT MONITOR VGA SPOT MONITOR, SET CAMERAS OR AUTO CYCLE CAMERAS ON 2<sup>ND</sup> SCREEN
- SMART PHONE & TABLET FREE APPS FOR REMOTE VIEW AT THE APPLE AND ANDROID MARKETS
- DETECTION SETTINGS ADJUSTABLE MOTION, VIDEO TAMPERING AND VIDEO DETECTION
- BASIC ANALYTICS LINE CROSSING AND AREA DETECTION FOR MORE ACCURATE RECORDING
- ADVANCED ANALYTICS WHEN MATCHED WITH CAMERA, TEN MORE FEATURES INCLUDING FACIAL, VEHICLE, REGION ENTRANCE, REGION EXIT, UNATTENDED BAGGAGE, OBJECT REMOVAL,
  AUDIO EXCEPTION DETECTION. SUDDEN SCENE CHANGE AND PIR ALARM
- EMAIL/TEXT ALERTS CUSTOMIZE SETTINGS TO SEND EMAILS/TEXTS ALERTS ON EVENTS
- CMS SOFTWARE FREE SOFTWARE THAT ALLOWS MULTIPLE RECORDERS TO BE VIEWED AT ONCE
- **ZOOMING IN** ZOOM LIVE VIEW OR PLAYBACK WITH MOUSE TOGGLE
- RECORDING SCHEDULE CUSTOM PER CHANNEL RECORDING-24/7, MOTION OR BOTH ADJUSTABLE BY TIME AND DAY OF THE WEEK
- SMART SEARCH PLAYBACK SEARCH BY AREA, EVENT AND ANALYTICS FOR VIDEO RETRIEVAL
- USERS CREATE MULTIPLE USERS AND WITH CUSTOM PRIVILEGES FOR EACH USER
- OFF-SITE CONTROL ADJUST SETTINGS REMOTELY FROM A PC OR FREE CMS SOFTWARE
- **BUILT-IN POE** PLUG-N-PLAY, POWER AND AUTO CONNECT CAMERAS WITHIN 330FT FROM RECORDER OVER CAT5E OR CAT6 WITH RJ45 ENDS

## **ULTRA HD 4K NETWORK VIDEO RECORDER**

4KN8-8POE





### **Features**

- Ultra HD 4K HDMI Output
- 8 IP Channels of Recording
- Up to 12 Megapixels Recording per channel
- 8 Port Built-In PoE
- 1~16 Terabytes of Storage
- 1080p VGA Spot Monitor
- 80Mbps Incoming
- H.265/H.264+ Compression
  - o H.264+ / 50%-70% Hard Drive Savings
- No Per Channel Licensing Fee
- Rack Mountable
- Free iPhone / Android Apps
- Free CMS Remote Software
- Alarm Inputs-4/Output-1
- 3<sup>rd</sup> Party Camera Compatible
- ONVIF Compatible for 3<sup>rd</sup> party cameras
- Two-Way Audio
- Email / Text Notifications
- Smart Search Playback
- Line Crossing / Area Detection

| Model Number           | 4KN8-8POE  |
|------------------------|--|
| IP Channels            | 1~ 8 IP Channels   |
| Bandwidth              | 80 Mbps Input, 160 Mbps Output   |
| Video Compression      | H.265 / H.264+ / H.264 / MPEG4   |
| Video Output           | 1 HDMI, 1 VGA  |
| Audio                  | 8 Channels of Audio from Camera (mic or line-in)                       |
| Audio Input/Output     | 4 & 1  |
| Two-way Audio          | 1 & 1  |
| Record Resolution      | 1 Megapixel ~ 12 Megapixel Recording (Max of two 12 Megapixel Cameras) |
| HDMI Output Resolution | 4K, 3840×2160@30Hz, 2K 2560×1440@60Hz ~ 1024×768@60Hz                  |
| VGA Spot Monitor Res   | 1920×1080@60Hz, 1280×1024@60Hz, 1280×720@60Hz, 1024×768@60Hz           |
| Synchronous Playback   | 8ch, (2ch @ 4K, or 8ch @ 1080p)  |
| Network                | 1 RJ-45 10/100/1000 Mbps self-adaptive Ethernet Interface              |
| Built-in PoE           | 8 Port 802.3af PoE 10/100 Mbps PoE Network                             |
| VGA Spot Monitor       | Yes, Custom Views & Sequence   |
| Internal SATA          | 1 SATA interfaces  |
| HDD Storage            | 1TB ~ 16TB   |
| Alarm I/O              | 4 In, 1 Out  |
| USB interface          | 1 x USB2.0 and 1 x USB 3.0   |
| Operation Temperature  | -10 °C ~ +55 °C  |
| Rack Mountable         | Rack Ear Extensions  |
| Chassis                | 15.2"  |
| Dimension              | 15.2"W x 12.4"D x 2.0"H  |
| Power Supply           | 100 ~ 240VAC   |
| Weight                 | 6.6 lbs (without HDD)  |

