

# IP LICENSE PLATE RECOGNITION CAMERA

IPLPR2M2812



## Features

- 2 Megapixel (1920 x 1080)
- License Plate Recognition
- 60 Frames Per Second at HD 1080p
- Motorized 2.8-12mm Lens
- True Wide Dynamic Range 140dB
- 360ft EX-IR Range
- Facial Detection
- Intrusion Detection
- 3D Digital Noise Reduction
- Back Light Compensation
- IP67 Outdoor Rated
- Power over Ethernet (PoE)

Model Number	IPLPR2M2812
Resolution	2 Megapixel (1920 x 1080)
Image Sensor	1/2.8" progressive scan CMOS
Frame rate	60Hz: 60fps (1920 x 1080), 60fps (1280 x 720)
EX IR range	up to 360ft
Min. illumination	0.005 Lux @ (F1.4, AGC ON), 0 Lux with IR
Shutter time	1s ~ 1/100,000s
Lens	Motorized 2.8-12mm @ F1.4 angle of view: 114.5°~41.8°
Day & night	ICR
Digital noise reduction	3D DNR
Wide dynamic range	140dB
Backlight compensation	Yes, zone configurable
Video compression	H.264 / H.264+ / MJPEG / MPEG4
H.264 compression profile	Main profile
Bit rate	32 Kbps ~ 16 Mbps
Dual stream	Yes
Image settings	Adjustable through client software or web browser
On board Storage	Built-in Micro SD/SDHC/SDXC card slot, up to 128 GB
Audio	1 / 1
Alarm	1 / 1
Alarm trigger	Motion detection, tampering alarm
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP NTP, SNMP, HTTPS, FTP, 802.1x, Qos
System compatibility	ONVIF, PSIA, CGI
General functionalities	User authentication, watermark
Communication interface	1 RJ45 10M/ 100 M Ethernet interface
Operating conditions	-30°C ~ 60°C (-22°F ~ 140°F) humidity 90% or less (non-condensing)
Power supply	12 VDC ± 10%, PoE (802.3at)
Power consumption	Max. 15W
Ingress protection	IP67
Dimensions	3.93" x 4.09" x 12.28"
Weight	2000g (4.41 lbs)

\*\*Specifications improvements subject to change without notice